

CLAIMS

- 1 1. A method for detecting a correct transmission format upon encountering
2 a decoding error in a variable-format transmission scheme, wherein the
3 decoding error results from an unsuccessful decoding of a frame
4 including data, comprising:
5 prioritizing a plurality of permissible formats, resulting in a prioritized
6 order; and
7 decoding the data according to one or more of said permissible formats
8 in said prioritized order, and if said decoding according to one of said
9 permissible formats is successful, selecting the corresponding permissible
10 format as the correct transmission format.
- 1 2. The method of claim 1, wherein said prioritizing comprises:
2 determining a metric for each of said plurality of permissible formats; and
3 ordering said permissible formats according to said metrics to form said
4 prioritized order.
- 1 3. The method of claim 2, wherein the frame further includes a format
2 indication corresponding to a first format, wherein a permissible format
3 indication corresponds to each of said plurality of permissible formats,
4 and wherein said metrics are a function of the format indication and the
5 corresponding permissible format indication.
- 1 4. The method of claim 3, wherein said function comprises a Euclidean
2 distance between a first code word associated with said format indication
3 and a second code word corresponding permissible format indication.
- 1 5. The method of claim 3, wherein said function comprises a projection of a
2 first code word representing said format indication onto a Hadamard
3 space, wherein said Hadamard space includes code word vectors
4 representing said plurality of permissible format indications.

- 1 6. The method of claim 2, wherein the frame further includes a format
2 indication corresponding to a first format, wherein said metrics are a
3 function of historical format data.
- 1 7. The method of claim 6, wherein said historical format data comprises the
2 number of occurrences of said permissible formats during a first time
3 interval.
- 1 8. The method of claim 2, wherein said determining a metric comprises:
2 tracking a number of occurrences corresponding to each of said
3 permissible formats over a first time interval; and
4 calculating said metrics using said number of occurrences of the
5 corresponding permissible format.
- 1 9. The method of claim 8, wherein said first time interval ends prior to the
2 unsuccessful decoding of the frame.
- 1 10. The method of claim 2, wherein the frame is one of a plurality of frames
2 transmitting a block of data, wherein each of said metrics is at least a
3 function of the number of occurrences of the corresponding permissible
4 format over said block of data.
- 1 11. The method of claim 10, wherein the frame includes a plurality of sub-
2 channels, wherein a transport format combination indicator is associated
3 with each of said plurality of frames, and wherein each of said metrics is
4 further a function of said transport format combination indicators.
- 1 12. The method of claim 2, wherein said decoding comprises decoding the
2 data according to each of said permissible formats in said prioritized
3 order until the data is correctly decoded, or until said permissible formats
4 have been exhausted.
- 1 13. The method of claim 12, wherein only those permissible formats having a
2 metric within a first range are included in said prioritized order.

1 14. The method of claim 2, wherein said decoding comprises partially
2 decoding the data until it can be determined whether said decoding is
3 successful.

1 15. A method for decoding data upon encountering a transmission error in a
2 variable-format transmission scheme, wherein the error results from an
3 unsuccessful decoding of a frame including data, comprising:
4 determining a metric for each of a plurality of permissible formats;
5 prioritizing said permissible formats according to said metrics, resulting in
6 a prioritized order; and
7 decoding the data according to one or more of said permissible formats
8 in said prioritized order.

1 16. The method of claim 15, wherein said decoding comprises decoding the
2 data according to each of said permissible formats in said prioritized
3 order until the data is correctly decoded, or until said permissible formats
4 have been exhausted.

1 17. The method of claim 16, wherein said decoding further comprises
2 reporting an error to an upper application layer upon exhausting said
3 permissible formats.

1 18. A remote station apparatus comprising:
2 means for receiving a frame, wherein said frame includes data;
3 means for determining a metric for each of a plurality of permissible
4 formats upon the unsuccessful decoding of said frame; and
5 means for decoding said data according to one or more of said
6 permissible formats in order of said metrics, and if said decoding is successful,
7 for selecting the corresponding permissible format as the correct transmission
8 format.

1 19. The apparatus of claim 18, wherein said frame further includes a
2 received format indication, wherein a permissible format indication

3 corresponds to each of said plurality of permissible formats, and wherein
 4 said means for determining comprises means for calculating the
 5 Euclidean distance between the code words representing said received
 6 format indication and said permissible format indications.

1 20. The apparatus of claim 18, wherein said frame further includes a
 2 received format indication, wherein a permissible format indication
 3 corresponds to each of said plurality of permissible formats, and wherein
 4 said means for determining comprises means for projecting a first code
 5 word representing said received format indication onto a Hadamard
 6 space, wherein said Hadamard space includes code word vectors
 7 representing said plurality of permissible format indications.

1 21. The apparatus of claim 18, wherein said means for determining
 2 comprises:
 3 means for tracking a number of occurrences corresponding to each of
 4 said permissible formats over a first time interval; and
 5 means for calculating said metrics using said number of occurrences of
 6 the corresponding permissible format.

1 22. A computer readable media embodying a method for detecting a correct
 2 transmission format upon encountering a decoding error in a variable-
 3 format transmission scheme, wherein the decoding error results from an
 4 unsuccessful decoding of a frame including data, the method comprising:
 5 determining a metric for each of a plurality of permissible formats;
 6 prioritizing said permissible formats according to said metrics, resulting in
 7 a prioritized order; and
 8 decoding the data according to one or more of said permissible formats
 9 in said prioritized order, and if said decoding is successful, selecting the
 10 corresponding permissible format as the correct transmission format.

1 23. The computer readable media of claim 22, wherein the frame further
 2 includes a format indication corresponding to a first format, wherein a
 3 permissible format indication corresponds to each of said plurality of

4 permissible formats, and wherein said metrics are a function of the
5 format indication and the corresponding permissible format indication.

1 24. The computer readable media of claim 22, wherein said function
2 comprises a Euclidean distance between a first code word associated
3 with said format indication and a second code word corresponding
4 permissible format indication.

1 25. The computer readable media of claim 24, wherein said function
2 comprises a projection of a first code word representing said format
3 indication onto a Hadamard space, wherein said Hadamard space
4 includes code word vectors representing said plurality of permissible
5 format indications.

1 26. The computer readable media of claim 22, wherein the frame further
2 includes a format indication corresponding to a first format, wherein said
3 metrics are a function of historical format data.

1 27. The computer readable media of claim 22, wherein only those
2 permissible formats having a metric within a first range are included in
3 said prioritized order.

1 28. The computer readable media of claim 22, wherein said decoding
2 comprises partially decoding the data until it can be determined whether
3 said decoding is successful.

1 29. A wireless communication system comprising:
2 a transmitter configured to encode a frame according to a first
3 transmission format, wherein said first transmission format is selected from a
4 plurality of permissible formats; and
5 a receiver configured to:
6 receive said frame, wherein said frame includes a received format
7 indication,

8 decode said frame according to the transmission format
9 corresponding to said received format indication,
10 prioritize said plurality of permissible formats upon encountering a
11 decoding error with said frame, resulting in a prioritized order, and
12 decode said frame according to one of more of said plurality of
13 permissible formats in said prioritized order.

1 30. The wireless communication system of claim 29, wherein said receiver is
2 further configured to decode said frame according to each of said
3 plurality of permissible formats in said prioritized order until said frame is
4 correctly decoded, or until said permissible formats have been exhausted

1 31. The wireless communication system of claim 29, wherein said transmitter
2 is located with a base station, and wherein said receiver is located within
3 a user terminal.
1